


Single Row Tapered Roller Bearing

30200 Series-30205J2/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designacion **30205J2/Q**

Dimensiones principales (mm)

d1 25

D 52

B 16.25

Capacidades de carga básica (KN)

dyc (Cr) 35.5

stc (Cor) 33.5

Pu 3.45

Clasificaciones de velocidad (rpm)

Clasificaciones de 11000

velocidad

Limitar la velocidad 13000

Peso (kilogramos) 0.15

ISO335

Dimensiones (ABMA) 3CC

Dimensiones [mm]

D 25

d1 37.4

B 15

C 13

r1,2 (min) 1

r3,4 (min) 1

a 12

Dimensiones del pilar y del filete [mm]

da (máx.) 31

db (min) 31

Da (min) 44

Da (máx.) 46

Db (min) 48

Ca (min) **2**Cb (min) **3**

ra (máximo) 1

rb (máximo) 1

Valor

mi 0.37

Y 1.6

yo 0.9

GQZ high quality 30200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered

roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com