

Single Row Tapered Roller Bearing

30300 Series-30305J2



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designacion	30305J2
Dimensiones principales (mm)	
d1	25
D	62
B	18.25
Capacidades de carga básica (KN)	
dyc (Cr)	44.6
stc (Cor)	43
Pu	4.75
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	9000
Limitar la velocidad	12000
Peso (kilogramos)	0.26
ISO335	
Dimensiones (ABMA)	2FB
Dimensiones [mm]	
D	25
d1	41.5
B	17
C	15
r1,2 (min)	1.5
r3,4 (min)	1.5
a	13
Dimensiones del pilar y del filete [mm]	
da (máx.)	34
db (min)	32
Da (min)	54
Da (máx.)	55
Db (min)	57
Ca (min)	2
Cb (min)	3
ra (máximo)	1.5
rb (máximo)	1.5
Valor	
mi	0.3
Y	2
yo	1.1

GQZ high quality 30300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com