

Single Row Tapered Roller Bearing  
 31300 Tapered Roller Bearing-**31322XJ2** 

Designacion	<b>31322XJ2</b>
Dimensiones principales (mm)	
d1	110
D	240
B	63
Capacidades de carga básica (KN)	
dyc (Cr)	457
stc (Cor)	585
Pu	62
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	1900
Limitar la velocidad	2800
Peso (kilogramos)	12.0
ISO335	
Dimensiones (ABMA)	7GB
Dimensiones [mm]	
D	110
d1 □	176
B	57
C	38
r1,2 (min)	4
r3,4 (min)	<b>3</b>
a	72
Dimensiones del pilar y del filete [mm]	
da (máx.)	135
db (min)	125
Da (min)	188
Da (máx.)	226
Db (min)	224
Ca (min)	7
Cb (min)	25
ra (máximo)	<b>3</b>
rb (máximo)	2.5
Valor	
mi	0.83
Y	0.72
yo	0.4

**GQZ bearings wholesale high quality 31300 Single Row**

## Tapered Roller Bearing

31303 tapered roller bearings, the inner diameter is 17mm, the outer diameter is 47mm and the width is 15.5mm.

31330 tapered roller bearings, the inner diameter is 150mm, an outer diameter is 320mm and a width is 75mm.

32300 series tapered roller bearings features:

31300 series tapered roller bearings are characterized by strong load carrying capacity, smooth operation and long service life, which are widely used in automobile, engineering machinery, metallurgical equipment, mining machinery and other fields.

31300 series tapered roller bearings belong to a kind of roller bearings, its inner and outer ring raceway cross-section is conical, mainly to bear radial load mainly radial and axial combined load, at the same time, can also withstand tilting moment. The design of this type of bearing enables it to provide stable support and load carrying capacity in various applications, thus ensuring stable operation and long-term use of the equipment.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-  
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com