


Single Row Tapered Roller Bearing

32000 Series-32024X



WUXI GUANGQIANG BEARING TRADE CO.,LTD



Designacion	32024X
Dimensiones principales (mm)	
d1	120
D	180
B	38
Capacidades de carga básica (KN)	
dyc (Cr)	242
stc (Cor)	415
Pu	44
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	2400
Limitar la velocidad	3400
Peso (kilogramos)	3.25
ISO335	
Dimensiones (ABMA)	4DC
Dimensiones [mm]	
D	120
d1	150
B	38
C	29
r1,2 (min)	2.5
r3,4 (min)	2
a	39
Dimensiones del pilar y del filete [mm]	
da (máx.)	132
db (min)	131
Da (min)	161
Da (máx.)	170
Db (min)	173
Ca (min)	7
Cb (min)	9
ra (máximo)	2
rb (máximo)	2
Valor	
mi	0.46
Y	1.3
yo	0.7

GQZ high quality 32000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com