


Single Row Tapered Roller Bearing

33000 Series-33017/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designacion	33017/Q
Dimensiones principales (mm)	
d1	85
D	130
B	36
Capacidades de carga básica (KN)	
dyc (Cr)	183
stc (Cor)	310
Pu	34.5
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	3600
Limitar la velocidad	4800
Peso (kilogramos)	1.75
ISO335	
Dimensiones (ABMA)	2CE
Dimensiones [mm]	
D	85
d1 [mm]	107
B	36
C	29.5
r1,2 (min)	1.5
r3,4 (min)	1.5
a	26
Dimensiones del pilar y del filete [mm]	
da (máx.)	94
db (min)	92
Da (min)	118
Da (máx.)	122
Db (min)	125
Ca (min)	6
Cb (min)	6.5
ra (máximo)	1.5
rb (máximo)	1.5
Valor	
mi	0.3
Y	2
yo	1.1

GQZ high quality 33000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com