


Single Row Tapered Roller Bearing

33100 Series-33114/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD



Designacion	33114/Q
Dimensiones principales (mm)	
d1	70
D	120
B	37
Capacidades de carga básica (KN)	
dyc (Cr)	172
stc (Cor)	250
Pu	30
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	4000
Limitar la velocidad	5300
Peso (kilogramos)	1.70
ISO335	
Dimensiones (ABMA)	3DE
Dimensiones [mm]	
D	70
d1	94.8
B	37
C	29
r1,2 (min)	2
r3,4 (min)	1.5
a	28
Dimensiones del pilar y del filete [mm]	
da (máx.)	80
db (min)	79
Da (min)	104
Da (máx.)	112
Db (min)	115
Ca (min)	6
Cb (min)	8
ra (máximo)	2
rb (máximo)	1.5
Valor	
mi	0.37
Y	1.6
yo	0.9

GQZ high quality 33100 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com