


Single Row Tapered Roller Bearing

33200 Series-33219



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designacion	33219
Dimensiones principales (mm)	
d1	95
D	170
B	58
Capacidades de carga básica (KN)	
dyc (Cr)	374
stc (Cor)	560
Pu	62
Clasificaciones de velocidad (rpm)	
Clasificaciones de velocidad	2600
Limitar la velocidad	3800
Peso (kilogramos)	5.50
ISO335	
Dimensiones (ABMA)	3FE
Dimensiones [mm]	
D	95
d1	132
B	58
C	44
r1,2 (min)	3
r3,4 (min)	2.5
a	42
Dimensiones del pilar y del filete [mm]	
da (máx.)	107
db (min)	107
Da (min)	144
Da (máx.)	158
Db (min)	163
Ca (min)	9
Cb (min)	14
ra (máximo)	2.5
rb (máximo)	2
Valor	
mi	0.40
Y	1.5
yo	0.8

GQZ high quality 33200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com