


Four Point Angular Contact Ball Bearing

5200 Series-5203



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Designacion	5203
Dimensiones principales (mm)	
D	17
d	40
B	17.5
r (min)	0.6
Capacidades de carga básica (KN)	
Cr	14600
Cor	9050
Clasificaciones de carga básica (kgf)	
Cr	1490
Cor	920
Velocidad límite (rpm)	
Grasa	11000
Petróleo	15000
Distancia del punto de acción	
a0 (mm)	20.8
Dimensiones de instalación (mm)	
da (min)	22
Da (máx.)	35
ra (máximo)	0.6
Peso	
(kg)	0.09

GQZ high quality 5200 Series Four Point Angular Contact Ball Bearing

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com