
Four Point Angular Contact Ball Bearing

5200 Series-5215







Designacion	5215	
Dimensiones principales (mm)		
D	75	
D	130	
В	41.3	
r (min)	1.5	
Capacidades de carga básica (KN)		
Cr	93500	
Cor	83000	
Clasificaciones de carga básica (kgf)		
Cr	9550	
Cor	8500	
Velocidad límite (rpm)		
Grasa	3200	
Petróleo	4300	
Distancia del punto de acción		
a0 (mm)	66.1	
Dimensiones de instalación (mm)		
da (min)	84	
Da (máx.)	121	
ra (máximo)	1.5	
Peso		
(kg)	1.9	

## **GQZ high quality 5200 Series Four Point Angular Contact Ball Bearing**

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

## The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co., Learing.com-http://www.bearing-asia.c	Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbcom