

## Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7000DT,7000DF,7000DB,7000C 

## Bearing Numbers

Single row	<b>7000C</b>
DB	<b>7000DB</b>
DF	<b>7000DF</b>
DT	<b>7000DT</b>

## Dimensiones principales (mm)

D	10
D	26
B	8
r (min)	0.3
r1(min)	0.15

## Basic load ratings(N)

Cr	5300
Cor	2490

## Clasificaciones de carga básica (kgf)

Cr	540
Cor	254

## Valor

fo	12.6
----	------

## Velocidad límite (rpm)

Grasa	45000
Petróleo	63000



## Distance of action point(mm)



a	6.4
---	-----

## Abutment and fillet dimensions

da (min)	12.5
Da (máx.)	23.5
ra (máximo)	0.3

## Peso

(kg)	0.021
------	-------

## Basic load ratings(duplex bearing) (N)

Cr	8650
Cor	5000

## Basic load ratings(duplex bearing) (kgf)

Cr	880
Cor	510

## Limiting Speed(duplex bearing) (rpm)

Grasa	36000
Petróleo	50000

## Distance of action point (duplex bearing)(a0)

back-to-back arrangement	12.8
face-to-face arrangement	3.2

## Installation dimensions(duplex bearing)

db (min)	sesenta y cinco
Db(max)	24.8
rb (máximo)	0.15

## GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

**Model:7000 series**

**Bore (Inner) Diameter: 10 mm**

**Outer Diameter: 26 mm**

**Width (Thickness): 16mm;**

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

