

Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7009DT,7009DF,7009DB,7009A 

Bearing Numbers

Single row	7009A
DB	7009DB
DF	7009DF
DT	7009DT

Dimensiones principales (mm)

D	45
D	75
B	16
r (min)	1
r1(min)	0.6

Basic load ratings(N)

Cr	23100
Cor	18700

Clasificaciones de carga básica (kgf)

Cr	2360
Cor	1910

Valor

fo	15.7
----	------

Velocidad límite (rpm)

Grasa	9500
Petróleo	13000



Distance of action point(mm)



a	25.3
---	------

Abutment and fillet dimensions

da (min)	51
Da (máx.)	69
ra (máximo)	1

Peso

(kg)	0.25
------	------

Basic load ratings(duplex bearing) (N)

Cr	37500
Cor	37500

Basic load ratings(duplex bearing) (kgf)

Cr	3850
Cor	3800

Limiting Speed(duplex bearing) (rpm)

Grasa	7500
Petróleo	10000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	50.6
face-to-face arrangement	18.6

Installation dimensions(duplex bearing)

db (min)	50
Db(max)	70
rb (máximo)	0.6

GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

Model:7000 series

Bore (Inner) Diameter: 10 mm□

Outer Diameter: 26 mm□

Width (Thickness): 16mm;

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

