

Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7030DT,7030DF,7030DB,7030A 

Bearing Numbers

Single row	7030A
DB	7030DB
DF	7030DF
DT	7030DT

Dimensiones principales (mm)

D	150
D	225
B	35
r (min)	2.1
r1(min)	1.1

Basic load ratings(N)

Cr	137000
Cor	154000

Clasificaciones de carga básica (kgf)

Cr	14000
Cor	15700

Valor

fo	16.3
----	------

Velocidad límite (rpm)

Grasa	2400
Petróleo	3000



Distance of action point(mm)



a	71.6
---	------

Abutment and fillet dimensions

da (min)	162
Da (máx.)	213
ra (máximo)	2

Peso

(kg)	4.75
------	------

Basic load ratings(duplex bearing) (N)

Cr	222000
Cor	305000

Basic load ratings(duplex bearing) (kgf)

Cr	22700
Cor	31500

Limiting Speed(duplex bearing) (rpm)

Grasa	1900
Petróleo	2400

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	143.3
face-to-face arrangement	73.3

Installation dimensions(duplex bearing)

db (min)	sesenta y cinco
Db(max)	218
rb (máximo)	1

GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

Model:7000 series

Bore (Inner) Diameter: 10 mm□

Outer Diameter: 26 mm□

Width (Thickness): 16mm;

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.

