
Single Row Angular Contact Ball Bearings

7000 Series-7000DT,7000DF,7000DB,7000A







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Posring Numbers	
Bearing Numbers	70004
Single row	7000A
DB	7000DB
DF DT	7000DF 7000DT
Dimensiones principales	
D	10
D	26
B · (main)	8
r (min)	0.3
r1(min)	0.15
Basic load ratings(N)	5250
Cr	5350
Cor	2600
Clasificaciones de carga	
Cr	550
Cor	266
Valor	10.0
fo	13.2
Velocidad límite (rpm)	
Grasa	32000
Petróleo	43000
Distance of action point	
a	9.2
Abutment and fillet dim	
da (min)	12.5
Da (máx.)	23.5
ra (máximo)	0.3
Peso	
(kg)	0.019
Basic load ratings(duple	
Cr	8750
Cor	5200
Basic load ratings(duple	ex bearing) (kgf)
Cr	890
Cor	530
Limiting Speed(duplex b	
Grasa	24000
Petróleo	34000
Distance of action point	(duplex bearing)(a0)
back-to-back	18.4
arrangement	
face-to-face	2.4
arrangement	
Installation dimensions(duplex bearing)	
db (min)	11.2
Db(max)	24.8
rb (máximo)	0.15

GQZ high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com,shary@gqbearing.com