

Single Row Angular Contact Ball Bearings

7000 Series angular contact ball bearings-7019DT,7019DF,7019DB,7019C 

Bearing Numbers

Single row	7019C
DB	7019DB
DF	7019DF
DT	7019DT

Dimensiones principales (mm)

D	95
D	145
B	24
r (min)	1.5
r1(min)	1

Basic load ratings(N)

Cr	73500
Cor	73000

Clasificaciones de carga básica (kgf)

Cr	7500
Cor	7450

Valor

fo	15.9
----	------

Velocidad límite (rpm)

Grasa	6700
Petróleo	9000



Distance of action point(mm)



a	28.1
---	------

Abutment and fillet dimensions

da (min)	104
Da (máx.)	136
ra (máximo)	1.5

Peso

(kg)	1.42
------	------

Basic load ratings(duplex bearing) (N)

Cr	119000
Cor	146000

Basic load ratings(duplex bearing) (kgf)

Cr	12200
Cor	14900

Limiting Speed(duplex bearing) (rpm)

Grasa	5300
Petróleo	7500

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	561
face-to-face arrangement	8.1

Installation dimensions(duplex bearing)

db (min)	sesenta y cinco
Db(max)	139
rb (máximo)	1

GQZ bearing wholesale high quality 7000 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis.

Model:7000 series

Bore (Inner) Diameter: 10 mm□

Outer Diameter: 26 mm□

Width (Thickness): 16mm;

The 7000 series bearings contain models 7000CTA-2RZ/P5 single, 7001CTA-2RZ/P5 single, 7002CTA-2RZ/P5

single, 7003CTA-2RZ/P5 single, 7004CTA-2RZ/P5 single, 7005CTA-2RZ/P5 single, 7000CTA-2RZ/P4 single,

7001CTA-2RZ/P4 single, 7002CTA-2RZ/P4 single, 7003CTA-2RZ/P4 single, 7004CTA-2RZ/P4 single,

7005CTA-2RZ/P4 single. These models cover a wide range of specifications and configurations, including

single use and paired use, as well as different accuracy levels (P4 and P5) for a variety of application

scenarios. Models 7006CTA-2RZ/P4 paired and 7007CTA-2RZ/P4 paired are also available, providing

more options to meet different needs. These bearing types include angular contact ball bearings, which

are able to withstand radial and axial loads and can also operate at higher speeds, making them one of

the commonly used bearing types in mechanical systems.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com