
Single Row Angular Contact Ball Bearings

7200 Series-7204DT,7204DF,7204DB,7204A





BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Pooring Numbers		
Bearing Numbers	70044	
Single row	7204A	
DB	7204DB	
DF	7204DF	
DT	7204DT	
Dimensiones principales (mm)		
D	20	
D	47	
В	14	
r (min)	1	
r1(min)	0.6	
Basic load ratings(N)		
Cr	14500	
Cor	8300	
Clasificaciones de carga	básica (kgf)	
Cr	1480	
Cor	845	
Valor		
fo	13.8	
Velocidad límite (rpm)		
Grasa	17000	
Petróleo	22000	
Distance of action point	(mm)	
a	16.7	
Abutment and fillet dime	ensions	
da (min)	26	
Da (máx.)	41	
ra (máximo)	1	
Peso		
(kg)	0.106	
Basic load ratings(duple		
Cr	23500	
Cor	16600	
Basic load ratings(duple		
Cr	2400	
Cor	1690	
Limiting Speed(duplex b		
Grasa	13000	
Petróleo	19000	
Distance of action point		
back-to-back	33.3	
arrangement	55.5	
face-to-face	5.3	
	5.5	
arrangement	duplox boaring)	
Installation dimensions(
db (min)	25	
Db(max)	42	
rb (máximo)	0.6	

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com