


## Single Row Angular Contact Ball Bearings

7200 Series-7205DT,7205DF,7205DB,7205C



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

### Bearing Numbers

|            |               |
|------------|---------------|
| Single row | <b>7205C</b>  |
| DB         | <b>7205DB</b> |
| DF         | <b>7205DF</b> |
| DT         | <b>7205DT</b> |

### Dimensiones principales (mm)

|         |     |
|---------|-----|
| D       | 25  |
| D       | 52  |
| B       | 15  |
| r (min) | 1   |
| r1(min) | 0.6 |

### Basic load ratings(N)

|     |       |
|-----|-------|
| Cr  | 16600 |
| Cor | 10200 |

### Clasificaciones de carga básica (kgf)

|     |      |
|-----|------|
| Cr  | 1690 |
| Cor | 1040 |

### Valor

|    |    |
|----|----|
| fo | 14 |
|----|----|

### Velocidad límite (rpm)

|          |       |
|----------|-------|
| Grasa    | 22000 |
| Petróleo | 28000 |

### Distance of action point(mm)

|   |      |
|---|------|
| a | 12.7 |
|---|------|

### Abutment and fillet dimensions

|             |    |
|-------------|----|
| da (min)    | 31 |
| Da (máx.)   | 46 |
| ra (máximo) | 1  |

### Peso

|      |       |
|------|-------|
| (kg) | 0.143 |
|------|-------|

### Basic load ratings(duplex bearing) (N)

|     |       |
|-----|-------|
| Cr  | 27000 |
| Cor | 20400 |

### Basic load ratings(duplex bearing) (kgf)

|     |      |
|-----|------|
| Cr  | 2750 |
| Cor | 2080 |

### Limiting Speed(duplex bearing) (rpm)

|          |       |
|----------|-------|
| Grasa    | 17000 |
| Petróleo | 24000 |

### Distance of action point (duplex bearing)(a0)

|                          |      |
|--------------------------|------|
| back-to-back arrangement | 25.3 |
|--------------------------|------|

|                          |     |
|--------------------------|-----|
| face-to-face arrangement | 4.7 |
|--------------------------|-----|

### Installation dimensions(duplex bearing)

|             |                 |
|-------------|-----------------|
| db (min)    | sesenta y cinco |
| Db(max)     | 47              |
| rb (máximo) | 0.6             |

## **GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings**

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com