
## Single Row Angular Contact Ball Bearings

7200 Series-7213DT,7213DF,7213DB,7213B







## WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers	
Single row	7213B
DB	7213DB
DF	7213DF
DT	7213DT
Dimensiones principales (mm)	
D	65
D	120
В	23
r (min)	1.5
r1(min)	1
Basic load ratings(N)	
Cr	63500
Cor	52500
Clasificaciones de carga	básica (kgf)
Cr	6500
Cor	5350
Valor	
fo	15.4
Velocidad límite (rpm)	
Grasa	4300
Petróleo	6000
Distance of action point	(mm)
a	50.3
Abutment and fillet dimensions	
da (min)	74
Da (máx.)	111
ra (máximo)	1.5
Peso	
(kg)	1.05
Basic load ratings(duple	ex bearing) (N)
Cr	103000
Cor	105000
Basic load ratings(duple	ex bearing) (kgf)
Cr	10500
Cor	10700
Limiting Speed(duplex b	
Grasa	3400
Petróleo	4800
Distance of action point	
back-to-back	100.6
arrangement	
face-to-face	54.6
arrangement	
Installation dimensions(duplex bearing)	
db (min)	71
Db(max)	114
rb (máximo)	1
	_

## **GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings**

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com