
Single Row Angular Contact Ball Bearings

7200 Series-7216DT,7216DF,7216DB,7216A





BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers		
Single row	7216A	
DB	7216DB	
DF	7216DF	
DT	7216DT	
Dimensiones principales		
Dimensiones principales		
D	80 140	
B	26	
-	-•	
r (min)	2	
r1(min)	1	
Basic load ratings(N)		
Cr	89000	
Cor	76000	
Clasificaciones de carga	-	
Cr	9100	
Cor	7750	
Valor		
fo	15.4	
Velocidad límite (rpm)		
Grasa	5000	
Petróleo	7100	
Distance of action point	(mm)	
a	44.8	
Abutment and fillet dime	ensions	
da (min)	90	
Da (máx.)	130	
ra (máximo)	2	
Peso	_	
(kg)	1.46	
Basic load ratings(duple		
Cr	145000	
Cor	152000	
Basic load ratings(duple		
Cr	14700	
Cor	15600	
Limiting Speed(duplex b		
Grasa	4000	
Petróleo	5600	
Distance of action point		
back-to-back	89.5	
arrangement		
face-to-face	37.5	
arrangement		
Installation dimensions(duplex bearing)		
db (min)	86	
Db(max)	134	
rb (máximo)	1	

GQZ high quality 7200 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com