

Single Row Angular Contact Ball Bearings

7900 Series angular contact ball bearings-7932DT,7932DF,7932DB,7932C



Bearing Numbers

Single row	7932C
DB	7932DB
DF	7932DF
DT	7932DT

Dimensiones principales (mm)

D	160
D	220
B	28
r (min)	2
r1(min)	1

Basic load ratings(N)

Cr	106000
Cor	133000

Clasificaciones de carga básica (kgf)

Cr	10800
Cor	13500

Valor

fo	16.5
----	------

Velocidad límite (rpm)

Grasa	3800
Petróleo	5000



Distance of action point(mm)



a	39.4
---	------

Abutment and fillet dimensions

da (min)	170
Da (máx.)	210
ra (máximo)	2

Peso

(kg)	3.1
------	-----

Basic load ratings(duplex bearing) (N)

Cr	173000
Cor	265000

Basic load ratings(duplex bearing) (kgf)

Cr	17600
Cor	27000

Limiting Speed(duplex bearing) (rpm)

Grasa	3000
Petróleo	4000

Distance of action point (duplex bearing)(a0)

back-to-back arrangement	78.9
face-to-face arrangement	22.9

Installation dimensions(duplex bearing)

db (min)	sesenta y cinco
Db(max)	214
rb (máximo)	1

GQZ bearings wholesale high quality 7900 Series Single Row Angular Contact Ball Bearings

The dimensions of the 7900 series bearings are 10mm inner diameter, 22mm outer diameter and 6mm thickness.

The 7900 series bearings are angular contact ball bearings with specific dimensional parameters for application scenarios that require radial and axial loads. Specifically, the 7900 series has an inner diameter of 10mm, an outer diameter of 22mm, and a thickness of 6mm. This dimensional information is critical to selecting the right bearing and ensuring its proper mounting and use. In addition, the 7900 series bearings also have specific external dimensions and chamfer dimensions, such as the small chamfer r1 is 0.3mm, the large chamfer r1 is 0.15mm, these details are important to ensure the performance and service life of the bearings.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com