
Single Row Angular Contact Ball Bearings

7900 Series-7907DT,7907DF,7907DB,7907C







WUXI GUANGQIANG BEARING TRADE CO.,LTD

Decima Numbers	
Bearing Numbers	7907C
Single row	
DB	7907DB
DF	7907DF
DT	7907DT
Dimensiones principales	
D	35
D	55
В	10
r (min)	0.6
r1(min)	0.3
Basic load ratings(N)	10100
Cr	12100
Cor	9150
Clasificaciones de carga	
Cr	1230
Cor	930
Valor	
fo	15.7
Velocidad límite (rpm)	
Grasa	18000
Petróleo	24000
Distance of action point	(mm)
a	11
Abutment and fillet dim	ensions
da (min)	40
Da (máx.)	50
ra (máximo)	0.6
Peso	
(kg)	0.074
Basic load ratings(duple	ex bearing) (N)
Cr	19600
Cor	18300
Basic load ratings(duple	ex bearing) (kgf)
Cr	2000
Cor	1860
Limiting Speed(duplex bearing) (rpm)	
Grasa	14000
Petróleo	20000
Distance of action point	(duplex bearing)(a0)
back-to-back	22.1
arrangement	
face-to-face	2.1
arrangement	
Installation dimensions(duplex bearing)	
db (min)	sesenta y cinco
Db(max)	52.5
rb (máximo)	0.3

GQZ high quality 7900 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqb earing.com-http://www.bearing-asia.com