


Four Point Angular Contact Ball Bearing
 QJ200 Series Angular Contact Ball Bearing-QJ216 

Designacion	QJ216
Dimensiones principales (mm)	
D	80
D	140
B	26
r (min)	2
Capacidades de carga básica (KN)	
Cr	124000
Cor	236000
Clasificaciones de carga básica (kgf)	
Cr	12600
Cor	24100
Velocidad límite (rpm)	
Grasa	3600
Petróleo	5000
Distancia del punto de acción	
a0 (mm)	77
Dimensiones de instalación (mm)	
da (min)	90
Da (máx.)	130
ra (máximo)	2
Peso	
(kg)	1.85



GQZ bearings wholesale high quality QJ200 Series Four Point Angular Contact Ball Bearing

The characteristics of QJ200 angular contact ball bearings mainly include:

1 **Strong load carrying capacity:** able to withstand both radial and axial loads and have a large load carrying capacity. This makes angular contact ball bearings widely used in the field of industrial machinery.

2 **Good rigidity:** the structural design makes it has high rigidity, can keep stable running state, suitable for the occasions of high precision requirements.

3 **High speed:** the contact angle between the inner ring and outer ring is designed as 15° or 25°, which makes the friction small and the temperature rise low, so as to increase the speed of the bearing.

4 **High precision:** due to the structural design of angular contact ball bearings, their precision and repeat positioning accuracy are high, which is suitable for mechanical equipment requiring high precision.

5 **Easy installation and adjustment:** the inner and outer rings can be separated, so it is easy to install and adjust.

QJ200-Series-Angular-Contact-Ball-Bearing-QJ216

In addition, QJ200 angular contact ball bearings are characterized by compact structure, small space occupation and light weight, which can adapt to the needs of high-speed rotation, while the coefficient of friction is small, which can reduce the energy loss and improve the service life of the bearings.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com