


Single Row Angular Contact Ball Bearings

7300 Series-7301DT,7301DF,7301DB,7301A



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Bearing Numbers

Single row **7301A**DB **7301DB**DF **7301DF**DT **7301DT**

Dimensiones principales (mm)

D 12

D 37

B 12

r (min) **1**

r1(min) 0.6

Basic load ratings(N)

Cr 9450

Cor 4500

Clasificaciones de carga básica (kgf)

Cr 965

Cor 460

Valor

fo 12.7

Velocidad límite (rpm)

Grasa 18000

Petróleo 24000

Distance of action point(mm)

a 13.1

Abutment and fillet dimensions

da (min) 18

Da (máx.) 31

ra (máximo) **1**

Peso

(kg) 0.06

Basic load ratings(duplex bearing) (N)

Cr 15400

Cor 9000

Basic load ratings(duplex bearing) (kgf)

Cr 1570

Cor 915

Limiting Speed(duplex bearing) (rpm)

Grasa 15000

Petróleo 20000

Distance of action point (duplex bearing)(a0)

back-to-back 26.1

arrangement

face-to-face 2.1

arrangement

Installation dimensions(duplex bearing)

db (min) 17

Db(max) 32

rb (máximo) 0.6

GQZ high quality 7300 Series Single Row Angular Contact Ball Bearings

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com